

WEEP HOLE PRODUCT SPECIFICATION

2.5"dia. ABS

1.0 SCOPE

This Product Specification covers the performance requirements for earth retaining structures pertaining to weep holes and dewatering.

2.0 PRODUCT DESCRIPTION

2.1 Product Name and Part Number

<u>Product Name</u> <u>Part Number</u>

JET FILTER ABS; AVAILABLE IN GRAY, SLATE, CLAY, BROWN JF2.5ABS

3.0 MATERIALS

- 3.1 Flame Retardent Polycarbonate/ Acrylonitrile-Butadiene-Styrene
- 3.2 Housing and Components are U/V Resistance
- 3.3 Filter Media

1.Mirafi® FW300 geotextile is composed of high-tenacity monofilament polypropylene yarns, which are woven into a stable network such that the yarns retain their relative position.

| CBR Puncture Strength | ASTM D6241 | lbs (N) | 1250 (5563) |
|------------------------------|------------|-----------------|-------------|
| Apparent Opening Size (AOS)1 | ASTM D4751 | U.S. Sieve (mm) | 30 (0.60) |
| Percent Open Area | COE-02215 | % | 8 |
| Permittivity | ASTM D4491 | sec-1 | 1.5 |
| Permeability | ASTM D4491 | cm/sec | 0.13 |
| Flow Rate | ASTM D4491 | (gal/min/ft2) | 115 |
| | | l/min/m2 | (4685) |







US PAT #:

7,615,148



2.5"DIA. ABS PRODUCT SPECIFICATION

JET Filter components are 100% made in the USA and are compliant with the Buy American Clause.

PART#:

JF2.5ABS